

Product benefits

- ideal for older vehicles
- reduces oil consumption

Applications

MOL MSE 15W-40 motor oil is recommended to use in WE and Japanese cars with engines designed before 1989, and in four-stroke gasoline engines manufactured in EE, or wherever the specifications in the manual call for the listed or lower performance levels.

Unless otherwise instructed in the car operating manual the recommended drain interval is maximum 10.000 km, or one year.

Specifications and approvals

Viscosity grade: SAE 15W-40
API SF/CC
MIL-L-46152B

Product description

MOL MSE 15W-40 is prepared from highly refined base oils together with a balanced composition of additive package (detergent-dispergant, antioxidation, anti-corrosion, wear resistant and antifoam). To establish the suitable flow properties it also contains viscosity modifier and pour point depressant additives.

Typical properties

Properties	Typical values
Density at 15°C [g/cm ³]	0,885
Kinematic viscosity at 40°C [mm ² /s]	108,0
Kinematic viscosity at 100 °C [mm ² /s]	14,6
Viscosity index	132
Pour point [°C]	-30
Flash point (Cleveland) [°C]	225
Base number (BN) [mg KOH/g]	5,1

The characteristics in table are typical values of the product and do not constitute a specification.

Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

Engine oils are finished lubricant formulations where additional additives are unnecessary and may result in unforeseeable adverse effects. The manufacturer and distributor shall not be held liable for such possible damages.

In the original container under the recommended storage conditions: 60 months

Inflammability hazard: Grade IV.

Recommended storage temperature: max. 40°C

Ordering information

SAP code and packaging:

13006450 1 l plastic bottle
13006451 4 l plastic can
13006452 60 l steel drum
13006449 216.5 l steel drum
13006793 Customer IBC

Order booking (toll-free):

Phone: 80/201-331 (between 07-16 h weekdays)